



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problems

QFA Absorptive Exterior Grade Curtain

Exterior Quilted Fiberglass Absorber

- Superior UV and Weather Resistance
- Available In Four Facing Colors
- Heavy-Duty Vinyl-Coated-Polyester Facing on Both Sides
- 2" Thick Fiberglass Core
- NRC Rating .75



Exterior Grade Quilted Fiberglass Absorbers reduce the reflection of sound waves by covering reflective surfaces with a suitably UV protected, porous, sound absorbing product. The exterior Quilted Fiberglass Absorber consists of a heavy-duty vinyl-coated-polyester facing on both sides of a 2" thick quilted fiberglass. Wall panels are constructed with grommets across the top and bottom, and are sewn with an exterior grade thread.

MATERIAL: Fiberglass core, faced with heavy-duty vinyl-coated-polyester (VCP) on both sides.

PATTERN: Quilted Diamond Pattern.

FEATURES: Effective, Durable, UV Resistant, Weather Resistant, Sound Absorbing.

APPLICATIONS: Exterior Grade faced quilted fiberglass absorbers are used to reduce reverberant noise on permanent outdoor applications such as enclosing HVAC equipment, dust collectors or similar machinery behind a manufacturing plant where UV resistance is required. It is commonly installed over wood fencing or on brick or masonry walls of buildings adjacent to a job site or a noisy piece of machinery.

PATTERN: 2".

TEMPERATURE RANGE: -40°F to +180°F

WEIGHT: 0.50 lb psf.

COLOR: Gray, Tan, Black, Beige.

INSTALLATION: Grommet Hangers.

Continued on next page.



Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: sales@acousticalsurfaces.com

Visit our Website: www.acousticalsurfaces.com

We Identify and S.T.O.P. Your Noise Problem

Absorptive Exterior Curtain – Sound Absorption Performance – ASTM C 423

	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	125Hz
2" Absorptive Exterior Curtain	.46	.94	.85	.64	.47	.33	.75

- Soundproofing Products • Sonex™ Ceiling & Wall Panels • Sound Control Curtains • Equipment Enclosures • Acoustical Baffles & Banners • Solid Wood & Veneer Acoustical Ceiling & Wall Systems
- Professional Audio Acoustics • Vibration & Damping Control • Fire Retardant Acoustics • Hearing Protection • Moisture & Impact Resistant Products • Floor Impact Noise Reduction
- Sound Absorbers • Noise Barriers • Fabric Wrapped Wall Panels • Acoustical Foam (Egg Crate) • Acoustical Sealants & Adhesives • Outdoor Noise Control • Assistive Listening Devices
- OSHA, FDA, ADA Compliance • On-Site Acoustical Analysis • Acoustical Design & Consulting • Large Inventory • Fast Shipment • No Project too Large or Small • Major Credit Cards Accepted